

DOCKLEVELLER SUPPLIES CC

MOBILE



RAMP



MOBILITY is Guaranteed with a MOBILE LOADING RAMP

GALVANISED SERRATED OPEN GRID TRACKS will give you a **RUST RESISTANT DECK** that will not retain water and will provide your forklift with a **SECURE SLIP RESISTANT** access to vehicle loading or offloading situations.



SOLIDLY CONSTRUCTED The Mobile Loading Ramp has a safe working capacity of 10,000kg.

It is **MOVED** by a forklift of two tons capacity (or more) enabling it to be used to offload several vehicles simultaneously or moved for out of the way storage.

USE on a regular **FLAT SURFACE** - no loading dock is necessary, **NO** extra civil costs, **NO** losses when you move premises - just take it with you. Minimal moving parts means Minimal Maintenance.



A simple Hydraulic Hand Pump lifts the front of the Ramp onto its **WHEELS** for ease of movement.
The forklift simply lifts the rear of the Ramp and guides it to the new position.

The **REINFORCED LIP** which is made in two halves for ease of handling provides for 150mm of Adjustment either **UP** or **DOWN**.
It also **FLOATS** automatically to absorb the movement of the Container Vehicle.



SPECIFICATIONS :	LENGTH	11000 mm
	WIDTH	2300 mm
	HEIGHT	1500 mm
HINGED LOADING RAMPS		150 mm UP/DOWN
CAPACITY		10000 kg
WEIGHT		4000 kg (approx.)



DOCKLEVELLER SUPPLIES operates a programme of continuous improvement and product development. For this reason specifications are likely to change from time to time and you should enquire about additional features that we may provide.

Manufactured by

DOCKLEVELLER SUPPLIES CC

Reg No CK 99/19914/23

Supplied throughout South Africa by branches or distributors in Johannesburg, Cape Town and Port Elizabeth.

DOCKLEVELLER SUPPLIES C.C.

8 Le Mans Place, Westmead, Durban

P.O. Box 178, New Germany, 3620

Tel: 031 700 6993 • Fax: 031 700 6994